

DURA 500 - 15 YEAR GUARANTEE APPLICATION

GENERAL INFORMATION

Building Owner: _____

Contact Name: _____ Phone: _____

Building Address: _____

City: _____ State/Province: _____ Zip/Postal: _____

Applicator/Contractor Name: _____ Phone: _____

ROOF INFORMATION

Roof Surface Type: _____ s Total Square Feet: _____

Roof Moisture Survey Conducted by: _____

Moisture Survey Attached: Yes ___ No ___ Attach Five Roof Photographs Prior to Application: Yes ___ No ___

Interior Drains: Yes ___ No ___ Number ___ Exterior Drains/Scuppers: Yes ___ No ___ Number ___

Ponding Water Areas ? Yes ___ No ___ Total Dimension of Ponding Water Areas: _____

Condition of Seams: _____

Condition of Roof Penetrations: _____

Condition of Flashings: _____

MATERIALS USED

	ROOFING FABRIC	450 SEAM SEALER	DURA 500
QUANTITY			
BATCH NUMBER			
DATE APPLIED			

Temperature and Weather Conditions on Day of Application: _____

By submitting this guarantee application, applicator hereby states that all materials have been installed in accordance with the latest published Dura 500 Specification Guideline by Superior Polymers Inc. Further, the Applicator understands that Superior Polymers Inc. or one of its Representatives may conduct customer satisfaction surveys with the Owner in regards to this project. **Note: Guarantee Application requests must be submitted within 30 days of job completion in order to qualify.**

Applicator Signature: _____ Print: _____ Date: _____

Company: _____

Address: _____ Zip/Postal: _____

Phone: _____ Email: _____

DURA 500 - 15 YEAR GUARANTEE APPLICATION

Instructions for filling out and submitting Guarantee Application

- (1) A minimum of 5 photos of the roof must be submitted to Superior Polymers Inc., prior to commencement of work. These must clearly show roof penetrations, problem seams, flashing condition and ponding water areas.
- (2) Roof surface types include: tar & gravel built-up roofing, smooth asphalt, rolled asphalt sheeting, torch-down rubberized asphalt sheeting (aka: modified bitumen/APP/SBS), ethylene propylene diene monomer (EPDM), PVC (Sarnafil®), thermoplastic olefin (TPO), chlorosulfonated polyethylene (CSPE or Hypalon®).
- (3) Batch numbers are located on small white label near top of the pail. Copy this number in the appropriate column of MATERIALS USED.
- (4) Completed guarantee application must be submitted to Superior Polymers Inc. within 30 days of job completion.